

Ozone
Only
Applications



Epoxy coated to prevent corrosion

FEATURES

- Full colour touch screen display
- Highest grade HEPA and carbon technology
- Automatic electronic flow control - maintains a constant extraction rate even as the filter blocks
- Gas and particle sensors to warn the operator
- Operate worldwide with no loss of performance

SPECIFICATIONS

Voltage	90v - 254v
Volume Part Number	1704132
Wattage	1.1kW
Frequency	50Hz / 60Hz
Cabinet Height	1195mm
Cabinet Width	528mm
Cabinet Depth	465mm
Cabinet Weight	70Kg
Sound Level	<60dBa
Airflow	400m ³ /h

INCLUDED AS STANDARD...

FILTERS



Main Filter Code
113450

Description
HEPA/
Twin Chemical



Pre-filter Code
111097

Description
F8/F9 Labyrinth



Pre-filter Code
200037

Description
Chemical
Absorbant Pad

FILTER MONITOR UNIT



Code
400470

Description
Ozone FMU

The ozone FMU will detect Ozone only and no other contaminants

CONNECTION KIT

Connection kit is included see overleaf for options

Find out more:

www.purex.co.uk

purex@purex.co.uk

+44 (0)1405 746030

OPTIONS

Connection Kits

Hose End Diameter

Hose Length

Purex Inlet Diameter

Code: 100043C


50mm

6m

80mm

Epoxy coated to prevent corrosion

Connect to 50mm diameter pipe/port or Purex valve
6.0m




Code: 120299

80mm

3m


80mm

Connect to 80mm diameter pipe/port
3.0m



If you do not see a connection kit that fits your machine or pipework, please contact Purex or your representative

Interfacing



Interfacing can remotely start the Purex machine when the connected machine starts.

Interfacing can also warn the connected machine when the Purex machine is in alarm.

Take a look through our Interfacing Guide to see our extensive range of options



Purex International Limited
QWP House, Island Drive
Capitol Park, Thorne
Doncaster, UK
DN8 5UE